

Угловые энкодеры MRP 5080, 5280, 5010

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: hia@nt-rt.ru || сайт: <https://heidenhain.nt-rt.ru/>

MRP 5000 series

Angle encoder modules with integrated encoder and bearing

- Compact dimensions
- High measuring and bearing accuracy
- Hollow shaft diameter: 35 mm

Encoder characteristics	Incremental MRP 5080	MRP 5280	Absolute MRP 5010
Measuring standard	OPTODUR circular scale		DIADUR circular scale
Signal periods	30000		16384
System accuracy*	±2.5" or ±5"	±2.5"	±2.5" or ±5"
Position error per signal period	±0.23"	±0.12"	±0.40"
Repeatability	From both directions: 0.3"		From both directions: 0.9"
RMS position noise	Typically 0.007"	Typically 0.004"	Typically 0.020"
Interface	~ 1 V _{PP}		EnDat 2.2
Ordering designation	–		EnDat22
Position values per revolution	–		28 bits
Clock frequency Calculation time t _{cal}	–		≤ 16 MHz ≤ 5 µs
Reference marks	80 (distance-coded)		–
Cutoff frequency –3 dB	≥ 500 kHz	≥ 300 kHz	–
Electrical connection	1.5 m cable with 15-pin D-sub connector; interface electronics inside connector		15-pin PCB connector; adapter cable plus quick connector as an accessory
Cable length	≤ 30 m (with HEIDENHAIN cable)		
Supply voltage	DC 5 V ±0.25 V		DC 3.6 V to 14 V
Power consumption (maximum)	5.25 V: ≤ 950 mW	5.25 V: ≤ 900 mW	3.6 V: ≤ 1.1 W 14 V: ≤ 1.3 W
Current consumption (typical)	175 mA (without load)	105 mA (without load)	5 V: 140 mA (without load)

* Please select when ordering



MRP 5080/MRP 5280



MRP 5010





MRP 5010
with cover

Bearing properties	Incremental MRP 5080	MRP 5280	Absolute MRP 5010
Shaft	Hollow through shaft D = 35 mm		
Max. permissible axial load ³⁾	200 N (centered load)		
Max. permissible radial load ³⁾	60 N		
Max. permissible tilting torque ³⁾	2.5 Nm		
Contact stiffness (values calculated)	Axial: 303 N/µm Radial: 181 N/µm	Axial: 364 N/µm Radial: 217 N/µm	Axial: 303 N/µm Radial: 181 N/µm
Contact stiffness (value calculated)	102 Nm/mrad	122 Nm/mrad	102 Nm/mrad
Mech. permissible speed	300 rpm	150 rpm	300 rpm
Moment of friction	≤ 0.025 Nm	≤ 0.045 Nm	≤ 0.025 Nm
Starting torque	≤ 0.015 Nm	≤ 0.025 Nm	≤ 0.015 Nm
Max. transferable shaft torque ³⁾	2 Nm		
Moment of inertia of rotor	0.13 · 10 ^{–3} kgm ²		
Radial guideway accuracy	Measured at a distance of h = 40 mm from the rotor mating surface: ≤ 0.20 µm (without load)		
Non-reproducible radial guideway accuracy	Measured at a distance of h = 40 mm from the rotor mating surface: ≤ 0.35 µm (without load)		
Axial guideway accuracy	≤ ±0.2 µm		
Axial runout of the shaft	≤ 5 µm		
Wobble of the axis	0.7"		
Vibration 55 Hz to 2000 Hz Shock 6 ms	≤ 200 m/s ² (EN 60068-2-6) ≤ 1000 m/s ² (EN 60068-2-27) (without load)		
Protection EN 60529 ²⁾	IP20		IP00 ¹⁾ or IP40
Operating temperature Storage temperature	0 °C to 50 °C 0 °C to 50 °C		
Relative air humidity	≤ 75% without condensation		
Mass	0.5 kg (without cable or connector)		

- ¹⁾ The electromagnetic compatibility of the complete system must be ensured through appropriate measures taken during installation.
²⁾ When mounted
³⁾ Purely static load, without additional vibrations or shock loads

MRP 5010



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: hia@nt-rt.ru || сайт: <https://heidenhain.nt-rt.ru/>